



## High-performance and cost-effective filter bags for *absolute* applications

Eaton's LOFCLEAR 100 filter bags are suitable for a wide range of applications such as the filtration of high-purity fluids with low particulate concentration, first-pass guard filtration, oil adsorption, activated carbon removal and many more.

LOFCLEAR 100 filter bags feature high-strength sewn, three-layer construction which is welded to the SENTINEL® seal ring. These filter bags have efficiencies of greater than 99% over a wide range of particle sizes, with dirt-holding capacities of up to 0.55 lbs (250 g).

### Features and benefits

- Layers of melt-blown polypropylene filter material help to clean fluid gradually and reliably
- Patented SENTINEL seal ring provides 100% bypass-free filtration
- 100% pure polypropylene fibers without any lubricants
- Spunbond cover layer virtually eliminates fiber release and migration
- Material is free from silicone and crater-forming substances<sup>1</sup>

- Enables *absolute* filtration in many applications where standard filter bags are currently used for cost reasons
- The fiber structure of the filter bag material breaks up gels and retains them within the material depth
- Eaton strongly recommends the use of an insertion tool that facilitates the insertion of the filter bag into the bag filter housing and ensures the correct alignment of the filter bag inside the restrainer basket

### Filter specifications

#### Material

Melt-blown polypropylene

#### Cover layer

Spunbond polypropylene

#### Seal ring

Welded polypropylene SENTINEL seal ring

#### Retention ratings<sup>2</sup>

4, 5, 10, 15, 20, 30, 40 µm  
@ >99% efficiency

### Dimensions/Parameters

#### Sizes

01: Ø 7 x 17" L (180 x 430 mm)  
02: Ø 7 x 32" L (180 x 810 mm)

#### Filter area

01: 2.6 ft<sup>2</sup> (0.24 m<sup>2</sup>)  
02: 5.2 ft<sup>2</sup> (0.48 m<sup>2</sup>)

#### Max. operating temperature

194 °F (90 °C)

#### Max. differential pressure

36.2 psi (2.5 bar)

#### Recommended change-out pressure for disposal<sup>3</sup>

11.6 – 21.7 psi (0.8 – 1.5 bar)

#### Max. flow rates<sup>4</sup>

01: 35 GPM (8 m<sup>3</sup>/h)  
02: 66 GPM (15 m<sup>3</sup>/h)



Powering Business Worldwide

# LOFCLEAR 100 Filter Bag Range


## Filter removal efficiency

Models size 01/02	Particle sizes (µm) at common removal efficiencies (%)				Δp psi (bar) size 02 @ 44 GPM (10 m³/h)	Max. operating temperature °F (°C)
	> 60%	> 90%	> 95%	> 99%		
113/123	0.5	1	2	4	0.4 (0.025)	194 (90)
114/124	0.75	2	3	5	0.3 (0.02)	194 (90)
115/125	1.5	3.5	8	10	0.2 (0.01)	194 (90)
116/126	2	6	13	15	< 0.2 (0.01)	194 (90)
118/128	25	35	37	40	< 0.2 (0.01)	194 (90)
119/129	15	25	27	30	< 0.2 (0.01)	194 (90)
130	6	14	15	20	0.7 (0.05)	194 (90)
135	1	6	8	10	0.3 (0.02)	194 (90)

## Welded SENTINEL seal ring



## Ordering information



<sup>1</sup> Based on an accepted paint compatibility test (see document QUC-STA-10).

<sup>2</sup> Reference values based on single pass tests in ambient lab conditions with ISO test dust in water at 44 GPM (10 m³/h)/size 02.

<sup>3</sup> Depending on the respective application requirements.

<sup>4</sup> For liquids with a dynamic viscosity of 1 mPa·s @ 68 °F (20 °C).

### North America

44 Apple Street  
Tinton Falls, NJ 07724  
Toll Free: 800 656-3344  
(North America only)  
Tel: +1 732 212-4700

### Europe/Africa/Middle East

Auf der Heide 2  
53947 Nettersheim, Germany  
Tel: +49 2486 809-0

### Intermornen Product Line

Friedensstraße 41  
68804 Altlußheim, Germany  
Tel: +49 6205 2094-0

### Begerow Product Line

An den Nahwiesen 24  
55450 Langenlonsheim, Germany  
Tel: +49 6704 204-0

### China

No. 3, Lane 280,  
Linhong Road  
Changning District, 200335  
Shanghai, P.R. China  
Tel: +86 21 5200-0099

### Singapore

4 Loyang Lane #04-01/02  
Singapore 508914  
Tel: +65 6825-1668

### Brazil

Av. Julia Gaioli, 474 – Bonsucesso  
07251-500 – Guarulhos, Brazil  
Tel: +55 11 2465-8822

For more information, please  
email us at [filtration@eaton.com](mailto:filtration@eaton.com)  
or visit [www.eaton.com/filtration](http://www.eaton.com/filtration)

© 2014 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

US  
EF-FTB-05a  
08-2014



Powering Business Worldwide

