

HOUSING OPERATION

Unfiltered liquid enters the housing above the filter bag, filling the interior of the housing and continuing through the bag. Solids are trapped inside the filter bag and are easily removed when the housing is serviced.

EB88 Single Liquid BAG HOUSINGS

EB88 Single Liquid Bag Housings remove dirt, pipe scale, and other contaminants from process liquids. Quality construction and design assure clean effluent and protection for all downstream equipment. Includes eye bolt closures.

APPLICATIONS

- Chemical
- General Industrial
- Oil and Gas
- Water

FEATURES

- Flow rates up to 220 gpm
- Accepts #2-size bag filters
- 304 Stainless Steel material, polished finish
- Factory hydro-tested
- Quick swing strap band closure
- Strainer baskets included
- EPDM seals, lid and basket
- Vent ports
- Bag hold down device
- Buna or Viton O-Rings available separately

SPECIFICATIONS

Pressure Rating	150 PSI
Connections	2-inch Flange
Housing Lid	Quick swing strap band closure
Lid Seal	EPDM
Inlets/Outlets	Side inlet/Bottom outlet
Construction/Finish	Stainless Steel w/polished finish
Bags Sizes	#2 liquid bags accepted
Base	Adjustable tripod leg assembly standard



EB88 SINGLE LIQUID Bag Housings

ORDERING INFORMATION

Part Number	Bag Size	Connection Size
EB88302FA415	#2	2" Flange

DIMENSIONS



