

Eaton's ECOLINE single bag filter housing is a light-weight design for commercial, OEM, non-hazardous, low-pressure applications that do not require a code stamp.

This single bag filter housing is a highly cost-effective solution for price-sensitive applications and features a handy V-clamp closure and threaded couplings. Units come standard with filter bag size 01 or 02 stainless steel restrainer baskets. Sizes 03 and 04 available in EMEA.

Features

- Side inlet with evacuation cover prevents spillage of unfiltered liquid, allowing for clean and easy filter bag change-outs
- V-clamp cover closure is easy to operate, allowing cover to be removed or closed quickly
- Compression hold down creates 360 degree sealing between the filter bag and the bag filter housing
- Designed with a 1/4" thread port on the lid for vent or gauge
- Smooth, bead-blasted finish makes it easy to completely clean the interior

Options

- Available in 316 stainless steel for high corrosion resistance.
 304 stainless steel version available in EMEA
- Adjustable mounting legs for simplified installation
- Multiple I/O connections to suit application





Unique, internal body-to-basket O-ring seal prevents bypass and is easy to maintain


ECOLINE Single Bag Filter Housing

Applications

Coarse filtration > 500 µm		
Medium filtration > 10 µm		
Fine filtration < 10 µm		

Pre-filtration	/
Safety filtration	
High volume	
Batch filtration	
Circuit filtration	
Continuous filtration	

••••••••	
Solvents, paints	
Fats and oils	
Catalyst, activated carbon	
Acids, bases	
Petrochemicals	
Water, waste water	✓
Chemical industry	
Pharmaceuticals	
Metal cleaning	✓
Automotive	
Electronics	
Food and beverage	
Paint and lacquer	
Water treatment	/



Dimensions - inch (mm)

Models	А	В	C	D	E
EBF-0101	22.88 (581)	7.68 (195)	19.64 (489)	5.37 (150)	37.00 (940)
EBF-0102	38.50 (977)	7.68 (195)	35.19 (884)	5.37 (150)	68.00 (1,727)
EBF-0103	14.56 (370)	4.50 (114)	11.81 (295)	3.50 (110)	24.00 (609)
EBF-0104	20.69 (525)	4.50 (114)	17.87 (454)	3.50 (110)	34.50 (876)

Dimensions for reference only and approximate. Exact dimensions for installation purposes available on request. Metric measures represent comparable products produced for EMEA and may not be an exact conversion from inches.

Technical data

Galvanic industry

Models	No. of filter bags	Size	Flow rate ¹ GPM (m³/h)	Max. pressure psi (bar)	Max. temp. °F (°C)	Housing volume gal (I)	Housing weight lb (kg)	I/O connections
EBF-0101	1	1	88 (20)	100 (6)	250 (120)	4.1 (15.5)	25 (7.5)	2" thread
EBF-0102	1	2	176 (40)	100 (6)	250 (120)	7.1 (27.0)	38 (11.0)	2" thread
EBF-0103	1	3	26 (6)	150 (9)	250 (120)	0.8 (3.0)	9 (3.5)	1 ¹ /2" thread
EBF-0104	1	4	53 (12)	150 (9)	250 (120)	1.2 (4.5)	11 (4.5)	1 ¹ /2" thread

Maximum theoretical flow based on water viscosity, filter bag specific.

Metric measures represent comparable products produced for EMEA and may not be an exact conversion from inches.

North America

44 Apple Street Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America only) Tel: +1 732 212-4700

Europe/Africa/Middle East Auf der Heide 2

53947 Nettersheim, Germany Tel: +49 2486 809-0

Internormen Product Line Friedensstraße 41 68804 Altlußheim, Germany Tel: +49 6205 2094-0

Begerow Product Line An den Nahewiesen 24 55450 Langenlonsheim, Germany Tel: +49 6704 204-0

China No. 3, Lane 280, Linhong Road Changning District, 200335 Shanghai, P.R. China Tel: +86 21 5200-0099

Singapore 4 Loyang Lane #04-01/02 Singapore 508914 Tel: +65 6825-1668

Av. Julia Gaioli, 474 - Bonsucesso 07251-500 - Guarulhos, Brazil Tel: +55 11 2465-8822

For more information, please email us at filtration@eaton.com or visit www.eaton.com/filtration

© 2014 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete. since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

US EF-FBH-14 10-2014



